

# High Flow Digital Tyre Inflator

## Single LCD Display



## XDB

The XDB is capable of achieving a flow rate of more than 3,000 litres/min and is specifically designed for quick inflation of large (OTR) tyres.

When use with a 4-way manifold kit, it can inflate multiple tyres simultaneously.

Suitable for use with standard or large bore valves and core extraction tools.

1/2" High Flow Valve

High Speed Inflation

Able to Inflate Multiple Tyres

Improves Productivity

Rugged and Durable Diecast Aluminium Enclosure

Large Backlight LCD Display

Vandal Resistant Mechanical Switches

Nitrogen Compatible

International Approvals

### Applications



Workshop



Tyre Shop




Truck / Fleet

## Options - Factory Fitted



Piezo Switches



Cabinet Heater



12V DC External Battery



Desktop Charging Unit

## Accessories - Supplied Separately



Manifold Kit - 4 Way



Core Retracting Tool



Air Filter / Auto-Drain / Regulator

## Technical Specifications

### Construction

Diecast Aluminium Enclosure

### Degree of Protection

IP66

### Power Requirement

12V AC/DC

100-120V AC 50/60Hz

220-240V AC 50/60Hz

### Units of Measurement

psi / kPa / bar / kg/cm<sup>2</sup>

### LCD Types

1 - psi / kPa / bar

2 - psi / kg/cm<sup>2</sup> / kPa

### Operating Range

5-145psi / 35-1000kPa / 0.3-10.0bar / 0.4-10.2kg/cm<sup>2</sup>

### Accuracy + or -

0.3psi / 2kPa / 0.02bar / 0.02kg/cm<sup>2</sup>

### Operating Temperature

Without heater

0°C to +60°C [32°F to 140°F]

With heater

-20°C to +60°C [-4°F to 140°F]

*Note : Outlet hose is not supplied with unit*

Refer to Airtec Corporation (Asia) Pte Ltd standard warranty terms and conditions.

Airtec Corporation (Asia) Pte Ltd reserves the right to change specifications, modify designs and discontinue items without obligation.

ÅTERFÖRSÄLJARE :

BOAB HJULDELAR AB

[www.boabhjuldelar.se](http://www.boabhjuldelar.se)

Tel. 0530 - 133 33

